



# RUBBER STONE POOL & SPA BINDER SAFETY DATA SHEET

## SECTION 1 PRODUCT & COMPANY IDENTIFICATION

### EW INDUSTRIES

Box 335

Imperial, SK S0G 2J0

1-888-799-3960 [www.CoverYourUgly.com](http://www.CoverYourUgly.com)

### TRANSPORTATION EMERGENCY

CALL CHEMTREC (24 hr): 800-424-9300

CANUTEC (24 hr): 613-996-6666

PRODUCT NAME: **Rubber Stone Pool & Spa Binder**

CHEMICAL FAMILY: Aliphatic Diisocyanate Prepolymer

CHEMICAL NAME: Aliphatic Diisocyanate Prepolymer

SYNONYMS: HMDI

RECOMMENDED USE: For Commercial use only.

RESTRICTIONS ON USE: Avoid water, alcohol, strong bases, substances and products that react with isocyanates.

## SECTION 2 HAZARD(S) IDENTIFICATION

### GHS CLASSIFICATIONS & HAZARD STATEMENTS:

Acute toxicity (Inhalation):	Category 2	Fatal if inhaled.
Skin irritation:	Category 2	Causes skin irritation.
Eye irritation:	Category 2	Causes serious eye irritation.
Respiratory sensitization:	Category 1	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization:	Category 1	May cause an allergic skin reaction.
Specific target organ toxicity - single exposure:	Category 3	(Respiratory system) May cause respiratory irritation.
Ecotoxicity:	Category 1	Very toxic to aquatic life with long lasting effects.

### PRECAUTIONS:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust/gas/ mist/vapors/sprays. In case of inadequate ventilation or exposures over the limit, wear respiratory protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell. IF EXPOSED: call a doctor. Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash with plenty of water and soap thoroughly after handling. IF ON SKIN: Wash with plenty of soap and water. A polyglycol-based skin cleanser or corn oil may be more effective than soap and water. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: get medical attention. Do not eat, drink, or smoke during work. Store locked up. Store in well ventilated place. Keep container tightly closed. Avoid release to the environment. Collect spillage. Dispose of contents and container in accordance with all Federal, State/Provincial and local laws and regulations.

### DANGER!



for spray applications and exposures above limits

This product is a “**Hazardous Chemical**” as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

<b>HAZARDOUS INGREDIENTS</b>		
<u>INGREDIENT</u>	<u>CAS NUMBER</u>	<u>CONCENTRATION (%)</u>
Dicyclohexylmethane-4,4'-Diisocyanate (HMDI)	<b>5124-30-1</b>	< 15 %
Alkanes, C14-C16, Chloro	<b>63449-39-8</b>	< 10%
Tin Compounds, Organic (as Tin)	<b>77-58-7</b>	< 1.0 %
Bis (1,2,2,6,6-Pentamethyl-4-Piperidiny) sebacate	<b>41556-26-7</b>	< 1.0 %
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	<b>82919-37-7</b>	< 1.0 %
<b>OTHER INGREDIENTS</b>		
Isocyanate prepolymer		< 90 %

### SECTION 4 FIRST AID MEASURES

#### **Most Important Symptom(s)/Effect(s)**

**Acute:** Isocyanate vapors or mist at concentrations above the exposure limits or guidelines can irritate (burning sensation) the mucous membranes in the respiratory tract (nose, throat, lungs) with symptoms of runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function (breathing difficulty). Persons with a preexisting, nonspecific bronchial hyperreactivity can respond to concentrations below the exposure limits or guidelines with similar symptoms as well as asthma attack or asthma-like symptoms. Exposure well above the exposure limits or guidelines may lead to bronchitis, bronchial spasm and pulmonary edema (fluid in lungs). Chemical or hypersensitivity pneumonitis, with flu-like symptoms (e.g. fever, chills), has also been reported. These symptoms can be delayed up to several hours after exposure. These effects are usually reversible.

May cause skin irritation with symptoms of reddening, itching, and swelling. Can cause sensitization. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash. Cured material is difficult to remove.

May cause eye irritation with symptoms of reddening, tearing, stinging, and swelling. May cause temporary corneal injury. Vapor or aerosol may cause irritation with symptoms of burning and tearing.

May cause irritation of the digestive tract; Symptoms may include abdominal pain, nausea, vomiting, and diarrhea.

**Delayed:** Symptoms affecting the respiratory tract can also occur several hours after overexposure.

**Eye Contact:** Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Remove contact lenses if present and easy to do. Get medical attention if irritation persists.. Suitable emergency eye wash facility should be immediately available.

**Skin Contact:** Immediately remove contaminated clothing and shoes. Remove material from skin immediately by washing with soap and plenty of water. Seek medical attention if irritation persists. Wash clothing before reuse. A polyglycol-based skin cleanser or corn oil may be more effective than soap and water. This may also apply to other isocyanates. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands. Suitable emergency safety shower facility should be available in work area.

**Inhalation:** Move person to fresh air, away from further exposure. Extreme asthmatic reactions that may occur in sensitized persons can be life threatening. Get medical attention immediately. Administer oxygen or artificial respiration as needed. Asthmatic symptoms may develop and may be immediate or delayed up to several hours. Call a physician or transport to a medical facility.

**Ingestion:** Do NOT induce vomiting. Rinse mouth and then drink plenty of water. Do not give anything by mouth unless the person is fully conscious. Get medical attention.

#### **Note to physician:**

Eyes: Stain for evidence of corneal injury. If cornea is burned, instill antibiotic/steroid preparation as needed. Workplace vapors could produce reversible corneal epithelial edema impairing vision. Skin: This compound is a skin sensitizer. Treat symptomatically

as for contact dermatitis or thermal burn. Ingestion: Treat symptomatically. There is no specific antidote. Inducing vomiting is contraindicated because of the irritating nature of the compound. Inhalation: Treatment is essentially symptomatic. An individual having a dermal or pulmonary sensitization reaction to this material should be removed from further exposure to any diisocyanate.

## SECTION 5 FIRE FIGHTING MEASURES

**FLASH POINT:**  $\geq 392^{\circ}\text{F}$  ( $200^{\circ}\text{C}$ ), not self-igniting

### EXTINGUISHING EQUIPMENT and MEDIA:

Dry chemical, Carbon dioxide (CO<sub>2</sub>), Foam, water spray for large fires.

**Extinguishing Media to Avoid:** Do not use direct water stream. May spread fire.

### SPECIAL FIRE FIGHTING PROCEDURES:

Firefighters should wear NFPA compliant structural firefighting protective equipment, including self-contained breathing apparatus and NFPA compliant helmet, hood, boots and gloves. Avoid contact with product. Decontaminate equipment and protective clothing prior to reuse. During a fire, isocyanate vapors and other irritating, highly toxic gases may be generated by thermal decomposition or combustion. Exposure to heated diisocyanate can be extremely dangerous.

### Hazardous Decomposition Products:

By Fire and High Heat: Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke., Isocyanate, Isocyanic Acid, Other undetermined compounds

### Unusual Fire/Explosion Hazards:

Closed container may forcibly rupture under extreme heat or when contents are contaminated with water (CO<sub>2</sub> formed). Use cold-water spray to cool fire-exposed containers to minimize the risk of rupture. Large fires can be extinguished with large volumes of water applied from a safe distance, since reaction between water and hot diisocyanate can be vigorous.

## SECTION 6 ACCIDENTAL RELEASE MEASURES

**MAJOR SPILL CONTACT:** EW Industries at (888) 799-3960

**TRANSPORTATION SPILL:** CHEMTREC at (800) 424-9300.

### PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment. Control the source of the leak. Contain the released material by damming, diking, retaining, or diverting into an appropriate containment area. Absorb or pump off as much of the spilled material as possible.

#### Environmental precautions:

Do not discharge into drains/surface waters/groundwater.

#### Methods and material for containment and cleaning up:

For small amounts: Absorb isocyanate with suitable absorbent material (see § 40 CFR, sections 260, 264 and 265 for further information). When using absorbent, completely cover the spill area with suitable absorbent material (e.g., vermiculite, kitty litter, Oil-Dri®, etc...). Allow for the absorbent material to absorb the spilled liquid. Shovel the absorbent material into an approved metal container (i.e., 55-gallon salvage drum). Do not fill the container more than 2/3 full to allow for expansion, and do NOT tighten the lid on the container. Repeat application of absorbent material until all liquid has been removed from the surface. Do NOT make container pressure tight. Move container to a well-ventilated area (outside). Spill area can be decontaminated with the following recommended decontamination solution: Mixture of 90 % water, 8 % concentrated ammonia, 2 % detergent. Add at a 10 to 1 ratio. Allow to stand for at least 48 hours to allow escape of evolved carbon dioxide.

For large amounts: If temporary control of isocyanate vapor is required, a blanket of protein foam or other suitable foam (available from most fire departments) may be placed over the spill. Transfer as much liquid as possible via pump or vacuum device into closed but not sealed containers for disposal.

For residues: The following measures should be taken for final cleanup: Wash down spill area with decontamination solution. Allow solution to stand for at least 15 minutes.

Additional Neutralization solutions:

Colorimetric Laboratories Inc. (CLI)- Isocyanate Decontamination Solution.

ZEP® Commercial Heavy-Duty Floor Stripper

Mix equal amounts of the following:

A 50-50 mixture of water and monoethanolamine

Mineral Spirits (80%), VM&P Naphtha (15%), and household detergent (5%)

**Note:** Always wear proper PPE when cleaning up an isocyanate spill and using a neutralization solution.

Avoid discharges into drains, water courses or onto the ground.

## SECTION 7 HANDLING & STORAGE

STORAGE TEMPERATURE: 50 °F (15 °C) - 95 °F (35 °C)

SHELF LIFE: 1 year

SPECIAL SENSITIVITY: No explosion proofing necessary. Substances to avoid include water, amines, strong bases, alcohols, copper alloys.

### HANDLING/STORAGE PRECAUTIONS:

Do not breathe vapors, mists, or dusts. Use adequate ventilation to keep airborne isocyanate levels below the exposure limits. Wear respiratory protection if material is heated, sprayed, used in a confined space, or if the exposure limit is exceeded. Warning properties (irritation of the eyes, nose and throat or odor) are not adequate to prevent overexposure from inhalation. This material can produce asthmatic sensitization upon either single inhalation exposure to a relatively high concentration or upon repeated inhalation exposures to lower concentrations. Individuals with lung or breathing problems or prior allergic reactions to isocyanates must not be exposed to vapor or spray mist. Avoid contact with skin and eyes. Wear appropriate eye and skin protection. Wash thoroughly after handling. Do not breathe smoke and gases created by overheating or burning this material. Decomposition products can be highly toxic and irritating. Store in tightly closed containers to prevent moisture contamination. Do not reseal if contamination is suspected.

Employee education and training in the safe use and handling of this product are required under the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### Note:

Pregnant or breastfeeding women must not handle this product. Store locked up.

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE LIMITS:

<u>INGREDIENT</u>	<u>CAS #</u>	<u>US. ACGIH Threshold Limit Values: Time Weighted Average</u>
Dicyclohexylmethane-4,4'-Diisocyanate	5124-30-1	(TWA): 0.005 ppm
Tin Compounds, Organic (as Tin)	77-58-7	OSHA PEL: (TWA) 0.10 mg/m <sup>3</sup>

Any component which is listed in section 3 and is not listed in this section does not have a known ACGIH TLV, OSHA PEL or supplier recommended occupational exposure limit.

### ENGINEERING CONTROLS: **Ventilation Measures:**

Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations to maintain levels below the TLV whenever this diisocyanate is heated, sprayed, or aerosolized. Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines. Exhaust systems should be designed to move the air away from the source of vapor/aerosol generation and people working at this point. The odor and irritancy of this material are inadequate to warn of excessive exposure.

**RESPIRATORY PROTECTION:** When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place. The recommended APR cartridge is an organic vapor/particulate filter combination cartridge (OV/P100). For emergency or non-routine, high exposure situations, including confined space entry, use a NIOSH-certified full face piece pressure demand self-contained breathing apparatus (SCBA) or a full face piece pressure demand supplied-air respirator (SAR) with escape provisions.

**General safety and hygiene measures:**

Wear protective clothing as necessary to prevent contact. Eye wash fountains and safety showers must be easily accessible. Observe the appropriate PEL or TLV value. Wash soiled clothing immediately. Contaminated equipment or clothing should be cleaned after each use or disposed of.

**EYE PROTECTION:** When directly handling liquid product, eye protection is required. Examples of eye protection include chemical safety goggles or chemical safety goggles in combination with a full face shield when there is a greater risk of splash.

**SKIN PROTECTION:** Avoid all skin contact. Depending on the conditions of use, cover as much of the exposed skin area as possible with appropriate clothing to prevent skin contact. Animal tests and other research indicate that skin contact with isocyanates can play a role in causing sensitization and respiratory reaction. Gloves should be worn, Nitrile rubber showed excellent resistance. Butyl rubber, neoprene and PVC are also effective.

**ADDITIONAL PROTECTION:** Emergency showers and eye wash stations should be available. Educate and train employees in the safe use and handling of this product. Follow all label instructions.

Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating.

**Note:**

Workers who have a history of adult asthma should be restricted from work with isocyanates. A history of eczema or respiratory allergies such as hay fever, are possible reasons for medical exclusion from isocyanate areas. Workers with a history of prior isocyanate sensitization should be excluded from further work with isocyanates. Once a worker has been diagnosed as sensitized to any isocyanate, no further exposure can be permitted.

<b>SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES</b>			
Appearance (physical state, color, etc.):	Yellow liquid, oily	Initial boiling point and boiling range:	392 °F (200 °C) @ 5 mmHg
Upper/lower flammability or explosive limits:	Not applicable	Flash point:	> 392 °F (200°C) (ASTM D92)
Odor:	musty	Evaporation rate:	No test data available
Odor threshold:	Not established	Flammability (solid, gas):	Not flammable
Vapor density:	Not applicable	Vapor pressure:	0.000015 mmHg (25°C)
pH:	Not Applicable	Partition coefficient: n-octanol/water:	Reacts with water
Relative density (specific gravity):	1.09 – 1.10 g/cm <sup>3</sup> @ 25 °C (77 °F)	Auto-ignition temperature:	Not self-igniting
Freezing point:	No test data available	Decomposition temperature:	Not established
Solubility(ies):	Insoluble - Reacts with water to liberate CO <sub>2</sub> gas	Viscosity:	3500 – 4500 mPa.s. (25°C)

**SECTION 10 STABILITY AND REACTIVITY**

---

**REACTIVITY:**

Contact with moisture, other materials that react with isocyanates, or temperatures above 350 °F (177 °C), may cause polymerization. Materials to avoid: Water, Amines, Strong bases, Alcohols, Metal compounds, strong oxidizers. Avoid moisture. Material reacts slowly with water, releasing carbon dioxide which can cause pressure buildup and rupture of closed containers. Elevated temperatures accelerate this reaction.

Avoid unintended contact with polyols.

**CHEMICAL STABILITY:**

This product is chemically stable under recommended storage conditions.

**OTHER:****Hazardous decomposition products :**

Decomposition products depend upon temperature, air supply and the presence of other materials. Gases are released during decomposition. By Fire and High Heat: Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke., Isocyanate, Isocyanic Acid, other undetermined compounds

**SECTION 11 TOXICOLOGICAL INFORMATION****Likely Routes of Exposure:**

Skin Contact  
Inhalation  
Eye Contact

**Health Effects and Symptoms**

**Acute:** Isocyanate vapors or mist at concentrations above the exposure limits or guidelines can irritate (burning sensation) the mucous membranes in the respiratory tract (nose, throat, lungs) with symptoms of runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function (breathing difficulty). Persons with a preexisting, nonspecific bronchial hyperreactivity can respond to concentrations below the exposure limits or guidelines with similar symptoms as well as asthma attack or asthma-like symptoms. Exposure well above the exposure limits or guidelines may lead to bronchitis, bronchial spasm and pulmonary edema (fluid in lungs). Chemical or hypersensitivity pneumonitis, with flu-like symptoms (e.g. fever, chills), has also been reported. These symptoms can be delayed up to several hours after exposure. These effects are usually reversible.

May cause skin irritation with symptoms of reddening, itching, and swelling. Can cause sensitization. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash. Cured material is difficult to remove.

May cause eye irritation with symptoms of reddening, tearing, stinging, and swelling. May cause temporary corneal injury. Vapor or aerosol may cause irritation with symptoms of burning and tearing.

May cause irritation of the digestive tract; Symptoms may include abdominal pain, nausea, vomiting, and diarrhea.

**Chronic:** As a result of previous repeated overexposures or a single large dose, certain individuals may develop sensitization to isocyanates (asthma or asthma-like symptoms) that may cause them to react to a later exposure to isocyanates at levels well below the exposure limits or guidelines. These symptoms, which can include chest tightness, wheezing, cough, shortness of breath or asthmatic attack, could be immediate or delayed up to several hours after exposure. Extreme asthmatic reactions can be life threatening. Similar to many non-specific asthmatic responses, there are reports that once sensitized an individual can experience these symptoms upon exposure to dust, cold air, or other irritants. This increased lung sensitivity can persist for weeks and in severe cases for several years. Sensitization can be permanent.

Prolonged contact with skin can cause reddening, swelling, rash, and, in some cases, skin sensitization. Animal tests and other research indicate that skin contact with isocyanates can play a role in causing isocyanate sensitization and respiratory reaction. This data reinforces the need to prevent direct skin contact with isocyanates.

Prolonged vapor contact with the eyes may cause conjunctivitis.

**Delayed:** Symptoms affecting the respiratory tract can also occur several hours after overexposure.

## **Toxicity Data for Dicyclohexylmethane-4,4'-Diisocyanate HMDI**

### Acute Oral Toxicity

LD50: 18200 mg/kg (rat, male/female)

### Acute Inhalation Toxicity

LC50: 0.434 mg/l, 4 h (rat, male/female) (OECD Test Guideline 403)

### Acute Dermal Toxicity

LD50: > 7000 mg/kg (rat, male/female) (OECD Test Guideline 402)

### Skin Irritation

rabbit, OECD Test Guideline 404, irritating

### Eye Irritation

rabbit, OECD Test Guideline 405, slight irritant

### Sensitization

inhalation: sensitizer (Guinea pig)

dermal: sensitizer (mouse, Mouse ear swelling test)

Skin sensitization according to Magnusson/Kligmann (maximizing test):: positive (guinea pig, OECD Test Guideline 406)

dermal: sensitizer (Human)

### Repeated Dose Toxicity

13 w, Inhalative: NOEL: 3 mg/m<sup>3</sup>, (rat, male/female, 6 hours a day, 5 days a week)

Evidence of damage to organs other than the organs of respiration was not found.

### Mutagenicity /Genetic Toxicity in Vitro:

Salmonella/microsome test (Ames test): No indication of mutagenic effects. (Metabolic Activation: with/without)

In vitro mammalian cell gene mutation test: negative (Chinese hamster V79 cell line, Metabolic Activation: with/without)

Chromosome aberration test in vitro: negative (Chinese hamster V79 cell line, Metabolic Activation: with/without)

### Toxicity to Reproduction/Fertility

Inhalative, 6 hours/day 7 days/week, (rat, male/female) NOEL (parental): 1 mg/m<sup>3</sup>,

### Developmental Toxicity/Teratogenicity

rat, female, Inhalative, 6 hours/day 7 days/week, NOEL (teratogenicity): 6 mg/m<sup>3</sup>, NOEL (maternal): 1 mg/m<sup>3</sup> Did not show teratogenic effects in animal experiments.

### Carcinogenicity:

No carcinogenic substances as defined by IARC, NTP and/or OSHA

## **Toxicity Data for Alkanes, C14-C16, Chloro (CAS# 63449-39-8)**

### Reproductive toxicity

May cause harm to breastfed babies.

## **SECTION 12 ECOLOGICAL INFORMATION**

### **Data based on the Ecological Data for Dicyclohexylmethane-4,4'-Diisocyanate (HMDI)**

#### Biodegradation

aerobic, 0 %, Exposure time: 28 Days, Not readily biodegradable.

#### Theoretical Biological Oxygen Demand (ThBOD)

2,195 mg/g

#### Acute and Prolonged Toxicity to Fish

LC50: 1.2 mg /l (Zebra fish (Brachydanio rerio), 96 h)

#### Acute Toxicity to Aquatic Invertebrates

EC0: > 8.3 mg/l (Water flea (Daphnia magna), 48 h)

#### Toxicity to Aquatic Plants

Material Name: Rubber Stone Pool & Spa Binder

EC50: > 5 mg/l, End Point: growth (Green algae (Scenedesmus subspicatus), 72 h)

Toxicity to Microorganisms

EC50: 19 mg/l, (Activated sludge microorganisms, 3 h)

**Data based on the Ecological Data for Alkanes, C14-C16, Chloro (CAS# 63449-39-8)**

Acute and Prolonged Toxicity to Fish

LC50: 0.06-0.08 mg/l, 96 hrs Rainbow trout, Donaldson trout (Oncorhynchus mykiss)

**SECTION 13 DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHOD:**

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator.

**EMPTY CONTAINER PRECAUTIONS:**

Empty containers retain product residue; observe all precautions for product. Do not heat or cut empty container with electric or gas torch because highly toxic vapors and gases are formed. Do not reuse without thorough commercial cleaning and reconditioning. If container is to be disposed, ensure all product residues are removed prior to disposal.

**SECTION 14 TRANSPORT INFORMATION**

**TRANSPORTATION EMERGENCIES:**

Contact should be made with EW Industries (888) 799-3960 or if for some reason there is no response, contact **CHEMTREC (800-424-9300)** when this product is unintentionally released from its container during its course of distribution, regardless of the amount released. Distribution includes transportation, storage incidental to transportation, loading and unloading. Such notification must be immediate and made by the person having knowledge of the release.

LAND Transport USDOT: **Non-Regulated\***

OCEAN Transport IMO / IMDG CODE:

UN NUMBER: UN3082

UN PROPER SHIPPING NAME: Environmentally hazardous substances, liquid, n.o.s. (Alkanes, C14-17, chloro)

HAZARD CLASS(ES) / LABEL: 9

PACKAGING GROUP: III

**AIR Transport IATA:**

UN NUMBER: UN3334

UN PROPER SHIPPING NAME: Aviation regulated liquid, n.o.s. (contains Dicyclohexylmethane-4,4'-Diisocyanate)

HAZARD CLASS(ES) / LABEL: Class 9, Miscellaneous

PACKAGING GROUP: III

REPORTABLE QUANTITY (RQ): 4,4'-methylenedi(cyclohexyl isocyanate) 5,000 lbs (2,270 kg)

*\*Additional DOT Transportation Information: (reference 49 CFR 172.101 Appendix A)*

*When in individual containers of more than the Product RQ, this material ships as **Regulated** as follows:*

UN NUMBER: NA3082,

UN PROPER SHIPPING NAME: Other Regulated Substance, Liquid, N.O.S. (contains Dicyclohexylmethane-4,4'-Diisocyanate)

HAZARD CLASS(ES) / LABEL: Class 9

PACKAGING GROUP: III

**SECTION 15 REGULATORY INFORMATION**

OSHA Hazcom Standard Rating: Hazardous

US. Toxic Substances Control Act: Listed on the TSCA Inventory.



CERCLA Reportable Quantity (RQ): Dicyclohexylmethane-4,4'-Diisocyanate 5 000 lbs (2270 kg)

US. EPA CERCLA Hazardous Substances Components none  
(40 CFR 302):

SARA Section 311/312 Hazard Categories: Acute Health Hazard

SARA Title III Section 302 Extremely Hazardous Substance none

SARA Title III Section 313 Toxic Chemicals Components(s):  
(40 CFR 372.65) – Supplier Notification Dicyclohexylmethane-4,4'-Diisocyanate CAS # 5124-30-1  
Required:

**State Right-To-Know Information:** For details on your regulatory requirements you should contact the appropriate agency in your state.

Massachusetts, New Jersey or Pennsylvania Right to Know Substance Lists:

<u>INGREDIENT</u>	<u>CAS NUMBER</u>	<u>CONCENTRATION (%)</u>
Dicyclohexylmethane-4,4'-Diisocyanate (HMDI)	5124-30-1	< 1.0 %

**California Prop. 65:**

To the best of our knowledge, this product does not contain any of the listed chemicals, which the state of California has found to cause cancer, birth defects or other reproductive toxins.

**SECTION 16 OTHER INFORMATION**

Contact: EW Industries  
Telephone: 888-799-3960  
MSDS Number:  
Origination Date: 7/18/2011  
Revision Date: 9/21/15  
Revision No.: 2

Information on this form is offered in good faith as typical values and not as a product specification. No warranty, either express or implied is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.